

CABS MODULE KIT



CERTIFICATIONS



FEATURES

Modules provide flexibility to select distance between phases and supports

Installs quickly and easily

Halogen free insulators

RoHS compliant

SPECIFICATIONS

Typical Application Current Rating	400 – 4,500 A
Max Working Voltage, IEC (Ui)	1,000 VAC;1,500 VDC
Finish	Electrogalvanized
Material	Steel;Glass Fibre Reinforced Polyamide
Complies With	IEC® 60439.1;IEC® 61439.1;IEC® 60695-2-11 (Glow Wire Test 960 °C)
Flammability Rating	UL® 94V-0
Working Temperature	-40 to 266 °F

Catalog Number	Item Name	Busbars per Phase	Busbar Width	Busbar Thickness	Depth(D)	Width(W)	Unit Weight
CABS4-5T-MOD	549370	1 – 4	1.180" – 4.920"	0.20"	1.540"	2.950"	0.860 lb
CABS2-10T-MOD	549380	1 – 2	1.180" – 4.720"	0.39"	1.540"	2.950"	0.820 lb

Catalog Number	Item Name	Busbars per Phase	Busbar Width	Busbar Thickness	Depth(D)	Width(W)	Unit Weight
CABS3-10T-MOD	549390	1 – 3	1.180" – 4.720"	0.39"	1.540"	3.940"	0.990 lb

ADDITIONAL PRODUCT DETAILS

CABS modules must be installed on CABS-APP Aluminium Profile.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europe

Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe

Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC

Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com **CADDY ERICO HOFFMAN RAYCHEM SCHROFF**
TRACER