

Control Cabinet Air Conditioner



Description

Order Number:	43100001
Brand Name:	COMPACT INDOOR
Colour:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress Protection:	IP 54 / TYPE 12
Approvals:	CE, cURus, cULus


Accessories:



[Stainless Steel Filter Holder 4305/08/09/10](#)



[Fibre Filter Media 4305/08/09/10](#)



[Washable Aluminium Filter 4305/08/09/10](#)




Technical Data

Cooling capacity L35L35 (EN14511-3):	1000 W @ 50 Hz 1080 W @ 60 Hz
Cooling capacity L35L50 (EN14511-3):	730 W @ 50 Hz 745 W @ 60 Hz
Compressor type:	Reciprocating compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	180 g / 6.3 oz
High / low Pressure:	29.5 / 6 bar 425 / 88 psig
Operating Temperature Range:	10°C - 55°C
Air flow volume (system / unimpeded):	Ambient air circuit: 410 / 850 m ³ /h Cabinet air circuit: 300 / 550 m ³ /h
Mounting:	Wall mounted
Dimensions A x B x C (D+E):	651.4 x 315 x 260 mm
Weight:	30 kg
Cut out dimensions:	635 x 275 mm
Voltage / Frequency:	230 V ~ 50/60 Hz
UL Voltage / Frequency:	230 V ~ 60 Hz
Current L35L35:	3.2 A
Starting current:	15.9 A
Max. current:	4.1 A
Nominal power L35L35:	550 W @ 50 Hz 640 W @ 60 Hz
Max. power:	820 W
Fuse:	10 A (T)
Short-circuit current rating:	5 kA
Connection:	Connection terminal block

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group COMPACT INDOOR - reliable and economical](#)

Performance graph:

[click image to enlarge](#)
Air flow:

[click image to enlarge](#)
Cut Out Dimension:

[click image to enlarge](#)

Order Information

Stainless steel housing part no.	4310002
With condensate evaporation part no.	43100101
Box dimensions	685 x 353 x 295 mm
Gross weight	31.5 kg
Taric code	84158200