




## Thermoelectric cooling unit



### Description

<b>Order Number:</b>	3155303
<b>Brand Name:</b>	SOLITHERM PELTIER
<b>Housing Material:</b>	Stainless steel AISI 304 (V2A)
<b>Ingress Protection:</b>	IP 66 / UL Type 12, 4, 4X
<b>Note:</b>	The torque for the mounting nuts should be 4.5 Nm.
<b>Approvals:</b>	CE, cURus
<b>Accessories:</b>	<div style="display: flex; align-items: flex-start;"> <div style="margin-right: 20px;">    </div> <div> <p><a href="#">Bimetallic temperature controller</a></p> <p><a href="#">Thermostat 301510</a></p> <p><a href="#">Condensate Kit 3152 / 3200</a></p> </div> </div>

## Technical Data

<b>Cooling capacity L35L35 (EN14511-3):</b>	125 W
<b>Operating Temperature Range:</b>	-20°C - 70°C
<b>UL temperature range:</b>	-20°C - 65°C
<b>Air flow volume (system / unimpeded):</b>	Ambient air circuit: 182 / 442 m <sup>3</sup> /h Cabinet air circuit: 58 / 168 m <sup>3</sup> /h
<b>Mounting:</b>	Recessed
<b>Dimensions A x B x C (D+E):</b>	306 x 203 x 160 (86+74) mm
<b>Weight:</b>	6.7 kg
<b>Cut out dimensions:</b>	260 x 160 mm
<b>Voltage / Frequency:</b>	24 V DC
<b>Current L35L35:</b>	7.5 A
<b>Starting current:</b>	11.3 A
<b>Max. current:</b>	8.6 A
<b>Nominal power L35L35:</b>	180 W
<b>Max. power:</b>	207 W
<b>Fuse:</b>	12 A (T)
<b>Connection:</b>	Connection terminal block

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SOLITHERM PELTIER - cooling without refrigerant](#)



## Order Information

<b>Stainless steel AISI 316 (V4A) housing part no.</b>	31553034
<b>Box dimension</b>	486.6 x 205 x 183.5 mm
<b>Gross weight</b>	11 kg
<b>Taric code</b>	84158300